

SCV-110D55W


Variable Type Vacuum Capacitor (VD55 Type)

Specification

Peak test Voltage	1 kVp (at 50, 60 Hz/ 1min)
RF Working Voltage	0.6 kVp
Capacitance nominal	40 – 1000 pF
Linear Variability	102 ± 6 pF/Turn (C ≥ 100 pF)
Maximum Current	36 Arms (13.56MHz)
Tuner Turns	10 ± 0.5 Turns
Tuner Operating Torque	0.15 Nm
Total Length	115 mm
Mounting Length	96.5 mm
Outer Diameter	φ55 mm
Weight	0.55 kg



Drawing




SCV-110D55W

Variable Type Vacuum Capacitor (VD55 Type)


MEIDEN

MQ90A40389


Frequency – Current response




Frequency – Voltage response




Frequency – ESR response




Frequency – tan δ response



Tuner Turns – Capacitance response



Capacitance – L & f response



Notice: Current collecting system: Capacitor both-end full-face collection.

Cooling System: Conduction Cooling.

Permissible surface temperature: 125°C.

(The surface temperature changes with current collecting conditions and ambient temperature.)

Ambient temperature: 25°C.

In regard to queries about these products, please contact below.

MEIDENSHA CORPORATION

Vacuum device Sales Department: ThinkPark Tower 2-1-1 Osaki, Shinagawa-ku, Tokyo, 141-6029 Japan

Phone: 81-3-6420-7590 Facsimile: 81-3-5745-3058 URL: <http://www.meidensha.co.jp>

As of Mar. 2023