

SCV-152.5


Variable Type Vacuum Capacitor (VM Type2 Type)

Specification

Peak test Voltage	15 kVp (at 50, 60 Hz/ 1min)
RF Working Voltage	9 kVp
Capacitance nominal	30 - 250 pF
Linear Variability	21 ± 2 pF/Turn (C ≥ 40 pF)
Maximum Current	100 Arms (13.56MHz)
Tuner Turns	12.0 ± 1.0 Turns
Tuner Operating Torque	0.245 Nm
Total Length	140 mm
Mounting Length	115 mm
Outer Diameter	φ62.4 mm
Weight	0.93 kg



Drawing




SCV-152.5

Variable Type Vacuum Capacitor (VM Type2 Type)

MEIDEN

MQ90A40398



Notice: Current collecting system: Capacitor both-end full-face collection.
Cooling System: Conduction Cooling.
Permissible surface temperature: 125°C.
(The surface temperature changes with current collecting conditions and ambient temperature.)
Ambient temperature: 25°C.

In regard to queries about these products, please contact below.

MEIDENSHA CORPORATION

Vacuum device Sales Department: ThinkPark Tower 2-1-1 Osaki, Shinagawa-ku, Tokyo, 141-6029 Japan

Phone: 81-3-6420-7590 Facsimile: 81-3-5745-3058 URL: <http://www.meidensha.co.jp>

As of Mar. 2023